



SITE SPREADER[®]

By Stoltz Mfg., LLC

Stoltz "Lowboy" Site Spreader

Portland cement, flyash, quicklime, bentonite or blends



Ideal unit for:

- Highway rehab;
- Parking lot base;
- Runway work;
- Street upgrades;
- Unpaved road maintenance;
- Full depth reclamation.

Features:

- Capacity: 15 tons;
- GVW: 35 tons;
- 5th wheel with air brakes;
- 61 HP Deutz engine/pump package;
- 8 ft wide spreading auger;
- 9 ft 7 in height x 101 in wide;
- Digital rate controller w/ radar;
- Scales and spray system optional;
- Completely road legal;
- In-cab consoles w/ 7-pin plugs.



Benefits:

- Spread accurately and get closer to spec —
- More accurate costings and lower wastage;
- More certainty in planning and less re-work;
- Low risk of section failure;
- Flexibility of having a dedicated spreader on-site;
- More efficient spreading process;
- Extend daily road-building capacity;
- Competitive qualitative advantage for bids and tenders;
- Potential pricing advantage for bids and tenders.
- 15 ton units — ideal for sites where cement is kept in silos on-site. Spread on demand.
- 25 ton units — ideal for sites where tankers deliver to site. Load entire tanker into unit once. Spread on demand.

For additional information, contact Stoltz at +610-286-5146 or email info@stoltzmfg.com

www.cementspreaders.com

© Stoltz Mfg., LLC Morgantown, PA USA 19543